

## **II. Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

### Listing of Claims:

1. (Pending) A cementing plug for use in cementing casing in a well, comprising:  
a body member defining a central opening therethrough;  
a [an elastomeric] jacket disposed around said body member and having a plurality of wiper [cup] cups extending therefrom, each said wiper cup having a conical outer surface extending upwardly and outwardly at an acute angle with respect to a longitudinal axis of the plug for engaging an inner surface of the casing; and  
an insert disposed across said central opening in said body member for closure thereof, said insert being one of a plurality of interchangeable inserts; [and]  
wherein said insert is a shearable member adapted for shearing and opening said central opening when a predetermined differential pressure is applied across said shearable member or a substantially non-shearable disk adapted for substantially permanent closure of said central opening.
2. (Pending) The plug of claim 1 wherein said shearable member is made of a rupturable material.
3. (Pending) The plug of claim 1 wherein said shearable member is a substantially flat disk having a substantially uniform thickness.
4. (Pending) The plug of claim 1 wherein said shearable member comprises:  
a ring portion; and  
a domed portion extending from said ring portion.

5. (Pending) The plug of claim 1 wherein:  
said body member defines a shoulder in said central opening; and  
said insert is disposed on said shoulder.
- 6-7. (Cancelled).
8. (Pending) A cementing plug for use in [a] cementing casing in a well, comprising:  
a body member defining a central opening therethrough and having a longitudinal axis;  
an elastomeric jacket disposed around said body member and having a plurality of wiper  
[cup] cups extending therefrom, each said wiper cup defining a conical outer surface extending  
upwardly and outwardly at an acute angle with respect to said longitudinal axis, wherein said  
outer surface is deflected into substantially cylindrical, wiping engagement with an inner surface  
of a casing when the plug is disposed therein; and  
an insert disposed in said central opening for at least temporary closure thereof, said insert  
being a selected one of a plurality of inserts; [and]  
wherein said insert is a shearable member adapted for shearing and opening said central  
opening when a predetermined differential pressure is applied across said shearable member or a  
substantially non-shearable disk adapted for substantially permanent closure of said central  
opening.
9. (Cancelled).
10. (Pending) The plug of claim 8 wherein said insert is positioned on a shoulder defined  
on said body member.
11. (Pending) A cementing plug apparatus for use in cementing a length of well casing  
in a well, said apparatus comprising:  
a pair of substantially identical plug subassemblies, each of said plug subassemblies  
comprising:  
a generally cylindrical body member defining a central opening longitudinally  
therethrough; and

an outer jacket disposed around said body member, said jacket having a plurality of resilient wiper [cup] cups extending therefrom adapted for wiping engagement with an inner surface of said length of casing;

a shearable insert positionable in one of said body members for temporarily closing said central opening in said one body member and for rupturing and thereby opening said central opening in response to a predetermined differential pressure thereacross; and

a substantially non-shearable insert positionable in the other of said body members for substantially permanently closing said central opening in the other body member.

12. (Pending) The apparatus of claim 11 wherein said jacket is made of an elastomeric material.

13. (Cancelled).

14. (Pending) The apparatus of claim 11 wherein each said wiper cup has an outer surface extending upwardly and outwardly at an acute angle with respect to a longitudinal axis of the corresponding body member.

15. (Pending) The apparatus of claim 11 wherein:  
said body member has a recess defined therein adjacent to said central opening;  
said shearable insert is positioned in the recess of said one of said plugs; and  
said non-shearable insert is positioned in the recess of the other of said plugs.

16. (Pending) The apparatus of claim 11 wherein said shearable insert comprises:  
a ring portion; and  
a domed portion extending upwardly and inwardly from said [outer] ring portion.

17. (Pending) The apparatus of claim 11 wherein said shearable insert comprises a substantially flat disk of substantially uniform thickness.

18. (Pending) The apparatus of claim 11 wherein said non-shearable insert comprises a substantially flat disk of substantially uniform thickness.

19. (Pending) A cementing plug apparatus for use in cementing casing in a well, said apparatus comprising:

a first cementing plug comprising:

a first body member defining a first central opening therethrough;

a first jacket disposed on said first body member, said first jacket having a plurality of wiper [cup] cups extending therefrom, each said wiper cup on said first jacket having a conical outer surface extending upwardly and outwardly at an acute angle with respect to a longitudinal axis of said first body member [adapted] for wiping engagement with an inner surface of the casing; and

a replaceable first insert disposed adjacent to said first body member for temporarily closing said first central opening and subsequently shearing when subjected to a predetermined pressure, thereby opening said first central opening; and

a second cementing plug comprising:

a second body member defining a second central opening therethrough;

a second jacket disposed on said second body member, said second jacket having a plurality of wiper [cup] cups extending therefrom, each said wiper cup on said second jacket having a conical outer surface extending upwardly and outwardly at an acute angle with respect to a longitudinal axis of said second body member [adapted] for wiping engagement with an inner surface of the casing; and

a replaceable second insert disposed adjacent to said second body member for substantially permanently closing said second central opening.

20. (Pending) The apparatus of claim 19 wherein:  
said first and [pond] second body members are substantially identical; and  
said first and second jackets are substantially identical.

21. (Pending) The apparatus of claim 20 wherein said second insert comprises a substantially flat disk.

22. (Pending) The apparatus of claim 19 wherein said first and second inserts are interchangeable.
23. (Pending) The apparatus of claim 19 wherein said first insert is a selected one of a plurality of inserts shearable at a corresponding plurality of predetermined pressures.
24. (Pending) The apparatus of claim 23 wherein said first insert comprises a substantially flat disk.
25. (Pending) The apparatus of claim 23 wherein said first insert comprises:  
an outer ring portion; and  
an inner domed portion integrally formed with said outer ring portion.
26. (Pending) The apparatus of claim 19 wherein said first and second jackets are made of an elastomeric material.
27. (Pending) The apparatus of claim 19 wherein:  
said plurality of wiper [cup] cups on said first jacket [is one of] comprises a pair of wiper cups; and  
said [second] plurality of wiper [cup] cups on said second jacket [is one of] comprises a pair of wiper cups.
28. (Cancelled).
29. (Pending) The apparatus of claim [28] 19 wherein said wiper cups are made of an elastomeric material.

30. (Pending) The apparatus of claim 19 wherein:  
said first body member defines a first shoulder therein;  
said second body member defines a second shoulder therein;  
said first [disk] insert is disposed on said first shoulder; and  
said second [disk] insert is disposed on said second shoulder.
31. (Pending) A plug for use in a well casing, comprising:  
a body member defining a central opening therethrough;  
a jacket disposed around said body member and having a plurality of wiper [cup] cups  
extending therefrom each said wiper cup having a conical outer surface extending upwardly and  
outwardly at an acute angle with respect to a longitudinal axis of the plug for engaging an inner  
surface of the casing; and  
an insert disposed in said central opening for at least temporary closure thereof, wherein said  
insert is a shearable member or a substantially non-shearable disk.
32. (Pending) The plug of claim 31 wherein said insert is one of a plurality of shearable  
and non-shearable inserts.
33. (Pending) The plug of claim 32 wherein said inserts are interchangeable.
34. (Pending) The plug of claim 31 wherein said insert is a substantially flat disk having  
a substantially uniform thickness.
35. (Pending) The plug of claim 31 wherein said shearable member is adapted for  
shearing and opening said central opening when a predetermined differential pressure is applied  
across said shearable member and said non-shearable disk is adapted for substantially permanent  
closure of said central opening.
36. (Pending) The plug of claim 31 wherein said shearable member is made of a  
rupturable material.

37. (Pending) The plug of claim 31 wherein said shearable member is one of a plurality of available thicknesses so that the shear pressure may be predetermined.

38-39. (Cancelled).

40. (Pending) The plug of claim 31 wherein said insert is positioned on a shoulder defined on said body member.

41. (Pending) The plug of claim 31 wherein said jacket is made of an elastomeric material.

42-43. (Cancelled).

44. (Pending) An apparatus [A plug for use in a well casing], comprising:

a cementing plug having:

a body member defining a central opening therethrough, the body member having a plurality of wipers that deflect into substantially cylindrical wiping engagement with the inner surface of a casing when the cementing plug is disposed therein; and

an insert positioned for at least temporary closure of said central opening, wherein said insert comprises:

an outer ring portion, and

an inner portion extending from said outer ring portion,

wherein said inner portion is an outwardly convex domed portion, is thinner than said outer ring portion and has a variable thickness.

45. (Pending) The apparatus [plug] of claim 44 wherein said outer ring portion and said inner portion are integrally formed.

46. (Pending) The apparatus [plug] of claim 44 wherein said outer ring portion and said inner portion form an internal corner.

47. (Pending) The apparatus [plug] of claim 46 wherein said corner is radiused.
48. (Pending) The apparatus [plug] of claim 44 wherein said inner portion has a first thickness at a center thereof and a second thickness at an outer portion thereof adjacent to said outer ring portion.
49. (Cancelled).
50. (Pending) The apparatus [plug] of claim 48 [49] wherein said domed portion has a height above said outer ring portion approximately equal to said first thickness.
51. (Pending) The apparatus [plug] of claim 48 wherein said first thickness is less than said second thickness.
- 52.–89. (Cancelled).
90. (Pending) The method of claim 92 wherein the wipers are acutely angled with respect to a longitudinal axis of the plug.
91. (Pending) The method of claim 92 wherein the wiper closest to the one end of the casing is overlapped by the other wiper.
92. (Pending) A method for wiping the inner surface of a casing comprising:  
providing a plug in the casing having at least two axially-spaced and overlapping wipers  
to engage and wipe the inner surface;  
applying pressure from one end of the casing to move the plug within the casing; and  
providing an insert across a central opening in the plug for closure thereof, wherein the  
insert is a shearable member adapted for shearing and opening the central opening when a  
predetermined pressure is applied across the shearable member or a substantially non-shearable  
member adapted for substantially permanent closure of the central opening.

93. (Pending) A method for wiping the inner surface of a casing comprising:  
providing a plug in the casing having at least two axially-spaced and overlapping wipers  
to engage and wipe the inner surface;  
applying pressure from one end of the casing to move the plug within the casing;  
providing an additional plug in the casing having at least two axially-spaced and  
overlapping wipers to engage and wipe the inner surface; and  
applying pressure from one end of the casing to move the additional plug within the  
casing.
94. (Pending) The method of claim 93 wherein the plugs are identical.
95. (Pending) The method of claim 93 wherein the wipers on each plug are acutely  
angled with respect to a longitudinal axis of each plug.
96. (Pending) The method of claim 93 wherein the wiper closest to the one end of the  
casing is overlapped by the other wiper on each plug.
97. (Pending) The method of claim 93 further comprising providing a shearable insert  
across a central opening in one plug for closure thereof and adapted for shearing and opening the  
central opening when a predetermined pressure is applied across the shearable insert, and further  
comprising providing a substantially non-shearable insert disposed across a central opening in  
the other plug for substantially permanent closure of the latter opening.
98. (Pending) A method for cementing a casing containing drilling mud in a well  
comprising:  
introducing a first plug into one end of the casing;  
introducing cement into the one end of the casing to force the first plug downwardly in  
the casing to displace the mud from the casing;  
providing at least two axially-spaced wipers on the first plug so that, as the plug passes  
downwardly in the casing, it wipes the inner surface of the casing of any accumulated mud;  
terminating the step of introducing the cement into the casing;

introducing a second plug into the casing end;  
forcing the second plug downwardly through the casing so that it forces the cement and  
the first plug downwardly in the casing;  
establishing a differential pressure across the first plug to open the first plug and allow  
the cement to pass through the first plug and exit the other end of the casing; and  
providing at least two axially spaced wipers on the second plug so that as the second plug  
passes downwardly in the casing, it wipes the inner surface of the casing of any accumulated  
cement; and  
sizing each wiper so that the wiper of each plug closest to the one end of the casing is  
overlapped by the other wiper of the same plug.

99. (Pending) The method of claim 98 wherein the first and second plugs are identical.

100. (Pending) The method of claim 98 further comprising providing a shearable insert  
across a central opening in the first plug for closure thereof and adapted for shearing and opening  
the central opening in the first plug when a predetermined pressure is applied across the  
shearable insert, and further comprising providing a substantially non-shearable insert across a  
central opening in the second plug for substantially permanent closure of the opening in the  
second plug.

101. (Pending) The method of claim 98 wherein the second plug is forced downwardly in  
the casing by introducing a fluid into the casing.

102. (Pending) The method of claim 98 wherein the second plug forces the cement from  
the casing into an annulus formed between the casing and the well.

103. (Pending) The method of claim 98 further comprising providing a float shoe in the  
casing which stops the downward movement of the first plug and causes the differential pressure.

104. (Pending) A cementing plug for use in cementing a casing in a well comprising:  
a plug having a longitudinal axis;

a first wiper extending radially outwardly from the plug at an acute angle with respect to the longitudinal axis of the plug;

a second wiper extending radially outwardly from the plug at an acute angle with respect to the longitudinal axis of the plug and disposed in an axially spaced relation to the first wiper;

wherein the second wiper overlaps the first wiper in an axial direction so that the outer surfaces of the wipers portions together extend continuously along the axial length of the body member before the plug is inserted in the casing; and

wherein the wipers deflect into substantially cylindrical, wiping engagement with an inner surface of the casing when the plug is inserted in the casing.

105. (Pending) The plug of claim 104 wherein the plug comprises a body member having an elastomeric jacket disposed therearound and wherein the first and second wipers are integrally formed with the jacket.

106. (Pending) The plug of claim 105 wherein the jacket comprises a cylindrical portion surrounding the body member and is integrally formed with the wipers.

107. (Pending) The plug of claim 105 wherein the body member is cylindrical and wherein the jacket has a through bore for receiving the body member.

108. (Pending) The plug of claim 104 further comprising an insert disposed across a central opening in the plug for closure thereof, wherein said insert is a shearable member adapted for shearing and opening the central opening when a predetermined pressure is applied across the shearable member or a substantially non-shearable member adapted for substantially permanent closure of the central opening.

109. – 141. (Cancelled)

142. (Pending) A cementing plug for use in cementing casing in a well, comprising:  
a body member defining a central opening through the plug;

a plurality of wiper cups extending from the plug, each said wiper cup having a conical outer surface extending upwardly and outwardly at an acute angle with respect to a longitudinal axis of the plug for engaging an inner surface of the casing;

an insert disposed across said central opening in said body member for closure thereof, said insert being one of a plurality of interchangeable inserts; and

wherein said insert is a shearable member adapted for shearing and opening said central opening when a predetermined differential pressure is applied across said shearable member or a substantially non-shearable disk adapted for substantially permanent closure of said central opening.

143. (Pending) The plug of claim 142 wherein said shearable member is made of a rupturable material.

144. (Pending) The plug of claim 142 wherein said shearable member is a substantially flat disk having a substantially uniform thickness.

145. (Pending) The plug of claim 142 wherein said shearable member comprises:  
a ring portion; and  
a domed portion extending from said ring portion.

146. (Pending) The plug of claim 142 wherein:  
said body member defines a shoulder in said central opening; and  
said insert is disposed on said shoulder.

147. (Cancelled).

148. (Pending) A plug for use in a well casing, comprising:  
a body member defining a central opening therethrough;  
a jacket disposed around said body member and having a plurality of wiper cups  
extending therefrom for engaging an inner surface of the casing; and

an insert disposed in said central opening for at least temporary closure thereof, wherein said insert is a shearable member comprising a ring portion and a domed portion extending from said ring portion or a substantially non-shearable disk.